

# TÜNEL DELGİ BİTLERİ

*DRIFTING &  
TUNNELLING*



delsondrill.com


TÜNEL DELGİ BİTLERİ / DRIFTING & TUNNELLING




# DRIFTING AND TUNNELING

## R25 (1") BIT THREAD

### Button bit

	Diameter		Buttons, mm			Angle	Flushing Hole		Weight approx kg	Part Number
	mm	in	Front No Size	Gauge No Size	Type		Front	Gauge		
	33	1 5/16"	2×7	5×7	-	35°	1	1	-	DLS-33R25
	35	1 3/8"	2×7	5×9	-	30°	1	1	-	DLS-35R25
	37	1 29/64"	2×7	5×9	-	30°	1	1	-	DLS-37R25
	38	1 1/2"	2×7	5×9	-	30°	1	1	-	DLS-38R25
	41	1 5/8"	2×8	5×9	-	35°	1	1	-	DLS-41R25

### Cross bit


	Diameter		Buttons, mm			Angle	Flushing Hole		Weight approx kg	Part Number
	mm	in	Front No Size	Gauge No Size	Type		Front	Gauge		
	33	1 5/16"	-	-	-	-	1	2	-	DLS-33R25-X
	35	1 3/8"	-	-	-	-	1	2	-	DLS-35R25-X
	38	1 1/2"	-	-	-	-	1	2	-	DLS-38R25-X




# DRIFTING AND TUNNELING

## R28 (1 1/8") BIT THREAD

### Button bit

	Diameter		Buttons, mm			Angle	Flushing Hole		Weight approx kg	Part Number
	mm	in	Front No Size	Gauge No Size	Type		Front	Gauge		
	38	1 1/2"	2×7	5×9	-	30°	1	1	-	DLS-38R28
	38	1 1/2"	2×7	5×9	-	35°	1	1	-	DLS-38R28-1
	41	1 5/8"	2×8	5×9	-	35°	1	1	-	DLS-41R28
	43	1 11/16"	2×8	5×10	-	30°	1	1	-	DLS-43R28


### Cross bit

	Diameter		Buttons, mm			Angle	Flushing Hole		Weight approx kg	Part Number
	mm	in	Front No Size	Gauge No Size	Type		Front	Gauge		
	38	1 1/2"	-	-	-	-	1	2	-	DLS-38R28-X
	41	1 5/8"	-	-	-	-	1	2	-	DLS-41R28-X


# DRIFTING AND TUNNELING

## R32 (1 1/4") BIT THREAD


### Button bit

	Diameter		Buttons, mm			Angle	Flushing Hole		Weight approx kg	Part Number
	mm	in	Front No Size	Gauge No Size	Type		Front	Gauge		
	43	1 11/16"	2×9	5×10	-	35°	1	2	-	DLS-43R32-29/510
	45	1 3/4"	2×9	5×11	-	30°	1	2	-	DLS-45R32-29/511
	48	1 7/8"	2×9	5×11	-	35°	1	2	-	DLS-48R32-29/511
	51	2"	2×10	5×12	-	35°	1	2	-	DLS-51R32-210/5112

### Button bit

	Diameter		Buttons, mm			Angle	Flushing Hole		Weight approx kg	Part Number
	mm	in	Front No Size	Gauge No Size	Type		Front	Gauge		
	43	1 11/16"	2×9	6×9	-	40°	2	2	-	DLS-43R32-29/69
	45	1 3/4"	2×9	6×10	-	35°	2	2	-	DLS-45R32-29/610


### Button bit

	Diameter		Buttons, mm			Angle	Flushing Hole		Weight approx kg	Part Number
	mm	in	Front No Size	Gauge No Size	Type		Front	Gauge		
	45	1 3/4"	3×8	6×10		30°	3	1	-	DLS-45R32-38/610
	48	1 7/8"	3×9	6×10		30°	3	1	-	DLS-48R32-39/610
	51	2"	3×9	6×10		35°	3	1	-	DLS-51R32-39/610


# DRIFTING AND TUNNELING

## R32 (1 1/4") BIT THREAD

### Button bit, Flat face

	Diameter		Buttons, mm			Angle	Flushing Hole		Weight approx kg	Part Number
	mm	in	Front No Size	Gauge No Size	Type		Front	Gauge		
		64	2 1/2"	4x10	8x10		-	35°		
	76	3"	4x11	8x11	-	35°	2	-	-	DLS-76R32-411/811

### Button bit, Drop center

	Diameter		Buttons, mm			Angle	Flushing Hole		Weight approx kg	Part Number
	mm	in	Front No Size	Gauge No Size	Type		Front	Gauge		
		102	4"	9x12	8x12		-	35°		